

LH 270 : Handheld hydraulic breaker (Hex28x152) (1 1/8x6)

1801 3643 56


[Create PDF sheet](#)
[Request information](#)

Contact

[View contact details](#)

Quick links

- ▶ [Atlas Copco Print Shop](#)
- ▶ [Atlas Copco Photo Archive](#)

Product information

Photos & Video

This powerful, high productivity breaker provide heavy-duty breaking in frozen soil, asphalt and reinforced concrete and are considered to be among the best in its class.

Features & benefits

- ▶ Low noise levels
- ▶ Slim design
- ▶ High power to weight ratio

Applications

- ▶ Medium and hard materials as asphalt and concrete

Technical data

Units: **Metric** [Imperial](#)

Technical Specifications	
Weight, incl. hoses	26.5 kg
Breaker Version	Standard
Shank Size (mm)	28x152
Shank Size (inch)	1 1/8x6
Length	765 mm
Oil flow	20 - 30 l/min
Working pressure	110 - 125 bar
Back Pressure, max	15 bar
Impact rate	1350 - 1750 blows/min
Vibration level 3 axes (ISO 28927-5), 10 lpm*	18.2 m/s²
Sound power level guaranteed, Lw (2000/14/EC)*	110 dB(A)
Sound pressure level (ISO 11203)* Lp, r=1m	95 dB(A)
EHTMA class	C/D

Product views

